



quality . experience . service

GT-XL-HF Final Filter

GT-XL-HF Final Filter

DRB Industries' **GT-XL-HF Final Filter** comes in a 17" (440mm) depth. This allows for higher dust holding capacity than the normal 12" depth final filters. It has 302 ft² of media (28m²), almost 100ft² more than standard filters. The **GT-XL-HF Final Filters** are water resistant. A Hot Glue separator ensures equal spacing between pleats. Rigid, Sturdy construction makes the filters durable, easy to ship, and easy to install. The **GT-XL-HF Final Filters** are fully incinerable, making disposal easy as well. It also has an ABS special draining design, and reinforcing grids downstream for extra burst protection. The **GT-XL-HF Final Filter** comes in a variety of efficiencies.



The only filter of its kind approved by all major OEMs for Offshore turbine applications

Specifications

Part #	FF-GTXL17F7	FF-GTXL17F9	FF-GTXL17H10
Nominal Size (W x H x D)	24" x 24" x 17"	24" x 24" x 17"	24" x 24" x 17"
Media Area	258 ft ²	258 ft ²	258 ft ²
Burst Pressure	30" w.g.	30" w.g.	30" w.g.
Efficiency	F7 (EN779:2002)	F9 (EN779:2002)	H10 (EN1822)

CONSTRUCTION			
Frame	ABS, special draining design	Sealant	Polyurethane, fully sealed 4 sides
Separator	Hot melt	Gasket	One piece expanded polyurethane
Media	Glass fiber paper, draining pleating patented	Grid	Glass fiber reinforcing grids downstream

Contact us for a quote



3104 South Elm Place, Suite I
Broken Arrow, OK 74012
Phone: 918.286.7176
Fax: 918.286.7215
sales@drbindustries.com
www.drbindustries.com

